【届出番号】27B2X00203199901

ClearJect®

–プラスチック製プレフィル用シリンジ–

製品仕様

●材質

- バレル　：環状ポリオレフィン（COP）
- チップキャップ　：ブチルゴム
- ピストン　：ブチルゴム、フッ素ラミネート
- プランジャーロッド　：ポリカーボネート、ポリプロピレン、ポリスチレン
- グリップ　：ポリプロピレン

●バレルサイズ表

<ルアーロックタイプ>

容量 (mL)	外径 (mm)	内径 (mm)	全長 (mm)
0.5	9.65	4.65	64.4
1.0	9.40	6.35	64.4
	11.20	6.35	64.4
2.25	11.20	8.65	64.4
3.0	11.20	8.65	84.4
5.0	15.05	12.45	79.0

<ルアーコーンタイプ >

容量 (mL)	外径 (mm)	内径 (mm)	全長 (mm)
1.0	9.15	6.35	64.5
2.25	10.85	8.65	64.4
5.0	15.05	12.45	79.0

ClearJect® WN

【認証番号】225AGBZX00025000

容量　：1mL、2.25mL
針　　：27G、29G (½" Thin wall)
　　22G-26Gも対応可

製造工程

クリーンな環境での全自動ライン製造

射出成形
↓
検査
カメラ検査による外観・寸法の全数保証
↓
シリコーンコート
・12,500cSt医療用グレード
・シリコーン有無検査装置による全数保証
↓
キャップ装着
↓
包装・γ線滅菌

包装仕様

■TASPACK®(RTUタイプ)
■γ線滅菌済み

※ご要望に応じた専用仕様にも対応致します。

大成化工株式会社
TEL:072-643-5791　FAX:072-640-2508
製品に関するお問い合せ　TEL:072-640-2500
〈URL〉https://www.taisei-g.co.jp　〈E-mail〉info@taisei-g.co.jp

(2024.08.26)

TAISEI KAKO

ClearJect®

【Approval No.27B2X00203199901】

-Plastic Prefillable Syringe-

Product Specification

●Materials

- Barrel : Cyclo Olefin Polymer
- Tip Cap : Butyl Rubber
- Piston : Chlorinated Butyl Rubber or Fluoro-Laminated Rubber
- Plunger Rod : Polypropylene, Polystyrene or Polycarbonate
- Grip : Polypropylene

●Barrel Size

<Luer Lock Type (LL)>

Volume (mL)	O.D. (mm)	I.D. (mm)	Total Length (mm)
0.5	9.65	4.65	64.4
1.0	9.40	6.35	64.4
	11.20	6.35	64.4
2.25	11.20	8.65	64.4
3.0	11.20	8.65	84.4
5.0	15.05	12.45	79.0

<Luer Cone Type (LC) >

Volume (mL)	O.D. (mm)	I.D. (mm)	Total Length (mm)
1.0	9.15	6.35	64.5
2.25	10.85	8.65	64.4
5.0	15.05	12.45	79.0

ClearJect® WN

【Approval No.225AGBZX00025000】

Volume : 1mL, 2.25mL

Needle : 27G, 29G (½" Thin wall) also applicable with 22G, 23G,25G and 26G

Production Process

Fully automated manufacturing under the clean condition.

Injection Molding

↓

Inspection

100% by camera(appearance, dimension)

↓

Siliconization

・12,500cSt Medical grade
・100% siliconization inspection by camera

↓

Tip cap Assembly

↓

Packing/Gamma Sterilization

Packing

■TASPACK®(RTU packing)
■Gamma Sterilization Finished

※Your required packing applicable.

If you are an overseas customer (outside Asia), please contact Gerresheimer as shown below:

URL: https://www.gerresheimer.com/

Phone: +49 5223 164 309 E-mail: clearject@gerresheimer.com

Person to contact : Mr. Bernd Zeiss

gerresheimer

(2024.08.26)